

## Technical solution sheet 6

# Falls through skylights, fragile roofs, voids and penetrations



### Planning a safe approach to solar installation

Many fatalities and serious injuries associated with installing solar panels are caused by people falling from a roof, through a roof, through an opening in a roof or while accessing a roof.

Not all areas of a roof are safely traversable. To help prevent risk of fatality or serious injury to solar workers while accessing or traversing roof areas, safe systems of work must be utilised.

Follow this four-step risk management process to ensure hazards are identified, risks are assessed and controlled, and that employers fulfil their duty to monitor, review and revise controls when required:

This is part of a series developed with WorkSafe to help installers in our programs work safely in the solar industry.

Use this sheet and others in this series to plan safe systems of work while installing photovoltaic systems.

#### In series 1:

- 1.1 Working safely at height during solar installations
- 1.2 Edge protection – Working at height
- 1.3 Manual handling of solar panels, heavy and bulky items
- 1.4 Working safely with ladders
- 1.5 Safe work practices using elevating work platforms
- 1.6 Falls through skylights, fragile roofs, voids and penetrations (this sheet)**
- 1.7 Working near asbestos-containing material

See: [solar.vic.gov.au/safety-and-quality](http://solar.vic.gov.au/safety-and-quality)

Figure 1: The four-step risk management process.





### Step 1: Identify hazards – determine if there is a fall risk

For both residential and small business solar installations, the first step in the risk management process is to identify hazards associated with working at height. This may include considering the location of skylights, fragile roofs, voids and penetrations within the work area.

Identification and assessment of these hazards should take into account the roof material and construction method to ensure the work area is capable of supporting workers, materials, tools and equipment.

It is important to determine:

- » the presence and condition of skylights, plastic roof sheeting and other brittle roof sheeting such as asbestos cement sheeting, rotted timbers, corroded metal, glass, slate, etc.
- » if a proprietary guardrail system can be installed to the edges of skylights, polycarbonate sheets or fragile roof areas to prevent access to these areas.

### Step 2: Assess risks – before working on a roof

Falling through a roof or skylight can be fatal or result in life-changing injuries. Employers have a duty to assess and control risks associated with a fall greater than two metres and document these in a safe work method statement (SWMS) due to the classification of such work as high-risk construction work (HRCW).

Employees undertaking PV system installations on a roof must be informed of and consulted on the risks and control measures contained in a SWMS.

See the WorkSafe website for more information on when and how to complete a SWMS for construction activities: [worksafe.vic.gov.au/resources/safe-work-method-statements-swms](https://www.worksafe.vic.gov.au/resources/safe-work-method-statements-swms)

When assessing the risk of falling through a roof while undertaking PV system installations, consider the following:

- » Identify any obvious holes or weaknesses on the roof.
- » Are there any skylights or other openings in the worksite vicinity?
- » Is there any damage to the roof or work surface such as water or fire damage?
- » Are there any areas of structural instability?

Stay vigilant – keep a look out for all risks throughout the duration of the work and take appropriate precautions when working in an unfamiliar work area.







4

### Step 3: Control risks – how can you manage the risk of falling through a roof?

Skylights, penetrations and fragile roof sheeting should be classified as non-trafficable areas – that is, areas that should not be walked on. Reasonably practicable control measures must be put in place to prevent solar workers from stepping or falling onto non-trafficable surfaces.

When the risk of a fall greater than two metres exists these control measures must, so far as is reasonably practicable follow the hierarchy of controls as stipulated in Regulation 44 of the Occupational Health and Safety Regulations 2017 (OHS Regulations).

Remember – the highest level of control is elimination of any risk associated with a fall at a workplace, for example, can some tasks be completed at ground level prior to being transferred to a roof?

Control measures could include:

- » Avoid accessing non-trafficable areas. When possible, work from a solid construction or elevating work platform to avoid standing on or near brittle and dangerous areas.
- » Install physical barriers around the non-trafficable areas, such as guard rails or suitably rated covers that are secured and labelled with warning signs.
- » Use temporary walkways or crawling boards of appropriate size and strength.
- » Install safety mesh secured under fragile roofing or skylights (see AS/NZS 4389:2015 *Roof safety mesh*).
- » As a last resort, install a fall arrest system which has adequately installed and maintained anchor points, along with ensuring employees are trained in its correct use.

### Step 4: Review and revise controls – during installation

Implementing control measures for falls during solar installations is not the end of the risk management process. An employer has a duty to review and, if necessary, revise control measures:

- » before making alterations to any plant or system of work that is likely to result in a fall
- » after a notifiable incident has occurred
- » if the control measures are inadequate
- » at the request of a Health and Safety Representative.

Some examples of control measures to constantly review and revise include:

- » Locating any skylights, roof hatches, vents, or other openings on the roof, and addressing the potential fall risks.
- » Ensuring roof material conditions are monitored for weakness or deterioration.
- » Training on how to safely navigate trip hazards while working on a roof.
- » Instruction on the correct use of equipment and materials that are going to be used on the roof.
- » Inspection of edge protection and fall protection systems (see *Technical Solution Sheet 1.2: Edge protection – Working at height*).

Finally, always make sure your employees are aware of all hazards on a roof where they are working and that adequate steps are taken to control risks.

Your actions shouldn't stop at Step 4. You should repeat this process often to make sure your management of risk is working.

*Image captions:*

1. Installation of roof walkway system to ensure safe access over skylights.
2. Fragile roof signage.
3. Installation of safety net protection for skylights on metal roofs.
4. Skylight protectors and access walkways provide safety and protection from the hazard of falling through a skylight, especially as they become brittle with age.

## Important resources

See the WorkSafe website for:

- » Compliance code: Prevention of falls in general construction: [worksafe.vic.gov.au/resources/compliance-code-prevention-falls-general-construction](https://www.worksafe.vic.gov.au/resources/compliance-code-prevention-falls-general-construction)
- » Compliance code: Prevention of falls in housing construction: [worksafe.vic.gov.au/resources/compliance-code-prevention-falls-housing-construction](https://www.worksafe.vic.gov.au/resources/compliance-code-prevention-falls-housing-construction)
- » A guide to falls prevention: [worksafe.vic.gov.au/resources/guide-falls-prevention](https://www.worksafe.vic.gov.au/resources/guide-falls-prevention)
- » Safe work method statements (SWMS): [worksafe.vic.gov.au/resources/safe-work-method-statements-swms](https://www.worksafe.vic.gov.au/resources/safe-work-method-statements-swms)

Also see:

- » Occupational Health and Safety Regulations 2017 (OHS Regulations): [legislation.vic.gov.au/in-force/statutory-rules/occupational-health-and-safety-regulations-2017](https://www.legislation.vic.gov.au/in-force/statutory-rules/occupational-health-and-safety-regulations-2017)

Australian Standards:

- » AS/NZS 4389:2015 *Roof safety mesh*

## Any questions?

Call WorkSafe on 1800 136 089 or email [info@worksafe.vic.gov.au](mailto:info@worksafe.vic.gov.au)

[worksafe.vic.gov.au](https://www.worksafe.vic.gov.au)

For more information about Solar Victoria's commitment to safety and quality, including training and workforce development, see: [solar.vic.gov.au/industry](https://www.solar.vic.gov.au/industry)

## Non-English speakers



If you'd like to speak to Solar Victoria in your language you can access free phone translation services by calling the National Translating and Interpreting Service on 131 450.

## Accessibility

If you would like to receive this publication in an alternative format, please contact Solar Victoria at [comms@team.solar.vic.gov.au](mailto:comms@team.solar.vic.gov.au)

This document is also available online at [solar.vic.gov.au](https://www.solar.vic.gov.au)

© The State of Victoria Department of Energy, Environment and Climate Action 2023.

### Disclaimer

This publication may be of assistance to you but the State of Victoria and its employees do not guarantee that the publication is without flaw of any kind or is wholly appropriate for your particular purposes and therefore disclaims all liability for any error, loss or other consequence which may arise from you relying on any information in this publication.

Developed with:

